

39 Ayer Road

Littleton, MA

(978) 540-2222

Candelabra 40W Equiv (5W LED)

- Lumens..... 300
- Watts..... 5
- Lumens per Watt..... 60
- Color Rendering Index..... 82
- Rated Life..... 25,000 hours
- M.O.L 3.8 inches (96.5 mm)
- Diameter 1.4 inches (35.6 mm)
- Input Line Voltage 120 VAC
- Minimum Starting Temperature -14°F (-26°)
- Power Factor >90%
- Dimmable.



A19 40W Equiv (6W LED)

- Lumens..... 460
- Watts..... 6
- Lumens per Watt..... 76.7
- Color Temperature..... 2700K (Warm)
- Rated Life..... 25,000 hours
- Dimmable.
- Omnidirectional Light
- 120V
- ENERGY STAR RATED



R20 50W Equiv (8W LED)

- Lumens..... 500
- Watts..... 8
- Lumens per Watt..... 62.5
- Color Rendering Index..... 82
- Color Temperature 2700K (Warm)
- Rated Life..... 25,000 hours
- M.O.L 3.5 inches (89 mm)
- Diameter 2.5 inches (64 mm)
- Minimum Starting Temperature -22°F (-30°C)
- Dimmable.
- 120V



A19 60W Equiv (10W LED)

- Lumens..... 800
- Watts..... 10
- Lumens per Watt..... 80
- Color Rendering Index..... 82
- Color Temperature 2700K (Warm)
- Rated Life..... 25,000 hours
- M.O.L 4.4 inches (112 mm)
- Diameter 2.4 inches (61 mm)
- Minimum Starting Temperature -22°F (-30°C)
- Dimmable.
- 120V
- ENERGY STAR RATED



Br30 65w Equiv (10W LED)

- Lumens..... 650
- Watts..... 9
- Color Rendering Index..... 80
- Color Temperature 2700K (Warm)
- Rated Life..... 25,000 hours
- Dimmable.
- 120V
- Medium Base E26 Standard
- ENERGY STAR RATED



A19 100W Equiv (15W LED)

- Lumens..... 1600
- Watts..... 18
- Color Rendering Index..... 80
- Color Temperature 2700K (Warm)
- Rated Life..... 25,000 hours
- Dimmable.
- 120V
- Medium Base E26 Standard
- ENERGY STAR RATED



Par38 120W Equiz (18W Outdoor LED)

- Lumens..... 1550
- Watts..... 18
- Color Temperature 3000K (Warm/Chaude)
- Rated Life..... 25,000 hours
- Minimum Starting Temperature -20°C
- Dimmable.
- 120V
- ENERGY STAR RATED



T8 4' LED 15W

- Lumens..... 1800
- Watts..... 15
- Color Temperature 4100K
- Color Rendering Index 80
- Rated Life..... 50,000 hours
- Non Dimmable.
- Voltage: 120-277VAC 50/60Hz
- Ballast Dependent

